




Technical data WEITZER SPORT 82 SPRUCE



Area-elastic sports flooring for sports and multi-purpose halls according to EN 14904 and DIN 18032-2; April 2001

Total construction height 82,6mm

- | | |
|------------------|--|
| 1) Sport parquet | <p>WEITZER SPORT 2245 PLY
3-strip multilayer parquet 2245x193x12,6mm
Hardwood top layer 3,6mm
Base from birch plywood, 7 layers
4-side T&G-profile
Finish PROSTRONG SPORT
Stapled to counter floor
Parquet front joints centred on counter floor
Stagger: min. 400mm</p> |
| 2) PE-Foil | <p>Creak protection foil
0,04mm thickness
Loosely laid with approx. 100mm overlay</p> |
| 3) Counter floor | <p>Spruce boards grade I/III 4-side planed, KD
4000x90x15mm
Distance/clear approx. 42mm
Stapled to elastic beam, joints centred
Stagger: min. 2 elastic beams</p> |
| 4) Elastic beam | <p>2-layer build-up 4000x60x65mm
With spruce boards, intermediate bar, elastic elements and supports
Spruce boards grade I/III 4-side planed, KD
Elastic pads from SPORT PUR cushion mat 10mm
Intermediate bars and supports from birch plywood</p> |

WEITZER SPORT parquet incl. certified substructure may only be installed on a subfloor that complies with the current standards and guidelines in accordance with the manufacturer's processing specifications. The subfloor must be sufficiently even, load-bearing, solid and dry. Appropriate building physics measures to protect against receding moisture must be taken prior to installation.