




Technical data WEITZER SPORT 35 OSB



Area-elastic sports flooring for sports and multi-purpose halls according to EN 14904 and DIN 18032-2; April 2001

Total construction height 34,6mm

1) Sport parquet

WEITZER SPORT 2245 PLY
3-strip multilayer parquet 2245x193x12,6mm
Hardwood top layer 3,6mm
Base from birch plywood, 7 layers
4-side T&G-profile
Finish PROSTRONG SPORT
Stapled to counter floor
Parquet front joints centred on counter floor
Stagger: min. 400mm

2) PE-Foil

Creak protection foil
0,04mm thickness
Loosely laid with approx. 100mm overlay

1) Load distribution strips

OSB strips 173x12mm with approx. 2600mm of length
T&G profile (glued) on short ends
Distance/clearance: 76,4mm
Centre distance: 249,4mm
Stagger: min. 400mm

3) Elastic layer

SPORT PUR cushion mat 10mm
Loosely laid (full surface), staggered

WEITZER SPORT parquet incl. certified substructure may only be installed on a subfloor that complies with the current standards and guidelines in accordance with the manufacturer's processing specifications. The subfloor must be sufficiently even, load-bearing, solid and dry. Appropriate building physics measures to protect against receding moisture must be taken prior to installation.

